



Issue date: 18-01-2023 Expiry date: 31-12-2023 Page 1 of 2

## 2 hr fire rated, 30Rw, Single leaf, Acoustic/Smoke/Fire doorset

## DESCRIPTION

Pyropanel AS-30-FRB-E is a 30 Rw, 2 hour fire rated 48mm nominal single leaf acoustic doorset that utilises a Pyropanel Euroseal<sup>®</sup> concealed perimeter seal and an approved bottom seal.

## APPLICATIONS

Ideal for applications that require up to 2 hours of fire resistance and an acoustic rating of 30 Rw.

## **FEATURES**

#### **Acoustic Rating**

30 Rw

#### **Fire Resistance**

Up to FRL -/120/30

#### **Smoke Resistance**

Meets the NCC requirement for a smoke door.

#### **Door Configuration**

Single leaf

#### Thickness

48mm (nominal)

#### **Door Weight**

Approx 22 kg/m<sup>2</sup>

#### Size

- Maximum Size 2700 x 1500mm (For Masonry, Concrete, Hebel and Plasterboard Walls).
- For other wall types, please contact your preferred Pyropanel distributor.

#### Frame

 Pyropanel filled Euroseal steel frame or Pyropanel fire rated timber frame (timber frame limited to 1hr applications, i.e -/60/30 and maximum door size of 2700 x 1020mm).

#### Finish

Plywood / MDF / Hardboard

#### **Perimeter Seals**

Pyropanel Euroseal<sup>®</sup> concealed smoke/acoustic seal.

#### **Bottom Seals**


See seal combinations listed on page 2.


## **OPTIONAL EXTRAS**

- Pre-hung in steel or timber frame.
- Approved veneer, steel or laminate facings.
- Pyropanel Pyrodur 13mm thick vision panels 300 x 200 or 600 x 100mm nom. (Rw 38)
- Note: Fire rating may be reduced by some of the optional extras. Contact your preferred distributor for clarification.

## INSTALLATION

Door frame must be tightly sealed to wall structure using Pyropanel Pyroseal sealant. Steel door frames require filling with fire rated plasterboard, Pyropanel light-weight M4 Mortar, concrete or mortar to achieve the desired acoustic rating.





Bottom seal - e.g Lorient LAS8001 (example only. See page 2 for complete list of seals.)

## **HOW TO SPECIFY**

"Door to be a Pyropanel AS-30-FRB-E acoustic door with -/120/30\* FRL, installed into a Pyropanel filled Euroseal® steel\* door frame, with Pyropanel Euroseal and Lorient LAS8001\* seals".

\* denotes example - delete, change or specify as required

#### **Distributed by:**

## ASSA ABLOY Australia Pty Ltd

235 Huntingdale Rd, Oakleigh, Vic 3166 Ph: (03) 9837 8500 Email: sales@pyropanel.com.au Web: www.pyropanel.com.au

ASSA ABLOY Australia P/L has a policy of continuous improvement and reserves the right to change methods and specifications without notice. Note: The Tech Sheet is an uncontrolled document. If printed please refer to the Tech-Sheet on the website to check if this document is valid.



Issue date: 18-01-2023 Expiry date: 31-12-2023 Page 2 of 2

# **ASSA ABLOY**

# 2 hr fire rated, 30Rw, Single leaf, Acoustic/Smoke/Fire doorset

## SEAL COMBINATIONS

Door Type	Perimeter Seals	Bottom Seals
AS-30-FRB-E	Pyropanel Euroseal®	Lorient LAS8001
		Lorient LAS8002
		Lorient LAS8003
		Lorient LAS8005
		Lorient LAS8006
		Lorient LAS8007
		Lorient LAS8008
		Lorient LAS8009

ASSA ABLOY AUSTRALIA Pty Ltd 235 Huntingdale Rd, Oakleigh, Vic 3166 Ph: (03) 9837 8500

Email: sales@pyropanel.com.au Web: www.pyropanel.com.au **Distributed by:** 

ASSA ABLOY Australia P/L has a policy of continuous improvement and reserves the right to change methods and specifications without notice. Note: The Tech Sheet is an uncontrolled document. If printed please refer to the Tech-Sheet on the website to check if this document is valid.